


Rechargeable Lithium-ion Battery Pack

ICR18650H2-2S3P

Electrical Characteristics

Nominal Capacity	7800mAh (0.2C Discharge)
Minimum Capacity	7500mAh (0.2C Discharge)
Nominal Voltage	7.4V
Charge Cut-off Voltage	8.4V
Discharge Cut-off Voltage	6.0V
Internal Impedance	$\leq 200\text{m}\Omega$
Standard Charge Current	0.2C
Standard Discharge Current	0.2C
Weight	Appro. 280g
Rapid Charge Current	0.5C (CC/CV, 3900mA, 8.4V, 78mA)
Max Discharge Current	0.5C (Ambient temperature 25°C)
Standard Charge Constant Current(CC) Charging at 0.2C to 8.4V Constant Voltage(CV) Charging at 8.4V to cut-off current $\leq 0.01\text{C}$	
Standard Discharge Constant Current (CC) Discharge at 0.2C to cut-off voltage of 6.0V	
General cycle Life(25 \pm 2°C)	300times
Constant current 0.2C charge to 8.4V, then constant voltage charge to current declines to 0.01C, rest 0.5h, then constant current 0.2C discharge to 6.0V, rest 0.5h. Repeat above steps till continuously discharging capacity lower than 70% of the Initial Capacities of the Cells.	



Thickness: 38mm Width: 56mm Height: 69mm

Drawings just for reference, any special demands, please don't hesitate to contact us.

Terminal / Connector

Soldering tabs/wires/connectors
(any special connector, please don't hesitate to contact us.)

Operating Temperature

Charge: 0 ~ 45°C
Discharge: -20 ~ 60°C

Storage Temperature

During 1 month: -5 ~ 35°C
During 6 months: 0 ~ 35°C

Note: Information above just for your reference, more details please contact Green Energy Battery Co., Ltd.