

Super Capacitor


HP-2R7-J107UY LL

Specification

Rate discharge capacitance (F 25°C $\Delta V=1.5V-1.25V$ $I=1A$)	100
Capacitance tolerance	-10%~+20%
Nominal Voltage U_0 (V)	2.7
Operating temperature range	-25°C~70°C
MAX.ESR(m Ω 1KHz)	25
Dimension(mm ϕ D x L)	22x45
Down-lead distance(mm P)	10 $\pm$ 1.0
Down-lead diameter(mm ϕ d)	1.0 $\pm$ 0.1
Cycle life Expectancy	Nominal voltage , 100,000 times charge-discharge circle $ \Delta C/C \leq 30\%$ of the initial value, ESR ≤ 4 times of the specified value(25°C)
Temperature characteristics	+70°C, $ \Delta C/C \leq 30\%$ of the initial value ESR $\leq$ specified value(25°C) -25°C, $ \Delta C/C \leq 50\%$ of the initial value ESR ≤ 4 times of the specified value(25°C)
High temperature load characteristics	+70°C ± 2 , nominal voltage, After 1000h $ \Delta C/C \leq 30\%$ of the initial value ESR ≤ 4 times of the specified value(25°C)
High temperature without load characteristics	Same with the High temperature load characteristics
Humidity Resistance	+40°C ± 2 , 90--95% RH , After 240h $ \Delta C/C \leq 30\%$ of the initial measured value IL ≤ 2 times of specified value (25°C) ESR ≤ 4 times of specified value (25°C)


Note:Information above just for your reference, more details please contact Green Energy Battery Co.,Ltd.

Figure and Dimension




Characteristics Test Results

(1). Temperature characteristics



(2). Life characteristics



Note: Information above just for your reference, more details please contact Green Energy Battery Co., Ltd.