


Rechargeable Lithium-ion Battery Pack

ICR18650H2-1S3P

Electrical Characteristics

Nominal Capacity	7800mAh (0.2C Discharge)
Minimum Capacity	7500mAh (0.2C Discharge)
Nominal Voltage	3.7V
Charge Cut-off Voltage	4.2V
Discharge Cut-off Voltage	3.0V
Internal Impedance	$\leq 200\text{m}\Omega$
Standard Charge Current	0.2C
Standard Discharge Current	0.2C
Weight	Appro. 130g
Rapid Charge Current	0.5C (CC/CV, 3900mA, 4.2V, 78mA)
Max Discharge Current	0.5C (Ambient temperature 25°C)
Standard Charge Constant Current(CC) Charging at 0.2C to 4.2V Constant Voltage(CV) Charging at 4.2V to cut-off current $\leq 0.01\text{C}$	
Standard Discharge Constant Current (CC) Discharge at 0.2C to cut-off voltage of 3.0V	
General cycle Life(25 \pm 2°C)	300times
Constant current 0.2C charge to 4.2V , then constant voltage charge to current declines to 0.01C, rest 0.5h , then constant current 0.2C discharge to 3.0V, rest 0.5h. Repeat above steps till continuously discharging capacity lower than 70% of the Initial Capacities of the Cells.	



Thickness: 19mm Width: 55.5mm Height: 69mm

(Note: Drawings just for reference)

Terminal /Connector

Soldering tabs/wires/connectors
 (any special connector, please
 don't hesitate to contact us.)

Operating Temperature

Charge: 0 ~ 45°C
 Discharge: -20 ~ 60°C

Storage Temperature

During 1 month: -5 ~ 35°C
 During 6 months: 0 ~ 35°C

Note: Information above just for your reference, more details please contact Green Energy Battery Co., Ltd.